

# Chiller Comparison Table

Range Name:	 <b>Warrior™</b>	 <b>Sentinel™</b>	 <b>Optimus™</b>
Best For:	Smaller, compact, indoor applications	Base level chilling of stable heat loads	Advanced level of chiller utilising two compressors for part load efficiency
Cooling Capacity Range	1.3kW to 4kW as standard Options up to 8kW	6kW to 110kW as standard	17kW to 211kW as standard Options up to 426kW
Warranty Term (b)	3 years	3 years	3 years
Commissioning Included (a)	Yes	Yes	Yes
Install Location	Indoor Only	Indoor/Outdoor	Indoor/Outdoor
Choice of Refrigerant	R134a	R410a	R410a
Optional Blygold Condenser Coating	✓	✓	✓
Evaporator Options	Brazed Plate Pack HX	Brazed Plate Pack HX	Brazed Plate Pack HX
Controller	Carel µChiller	Carel µChiller	Carel µChiller
Internal Buffer Tank	✓	✓	✓
Compressor Brand and Type	Tecumseh/Danfoss Reciprocating or Scroll	Copeland/Danfoss Scroll	Copeland/Danfoss Scroll
Capacity Control Steps	0 or 100%	0 or 100%	0, 50%, 100%
Expansion Device	Thermostatic Expansion Valve	Thermostatic Expansion Valve	Thermostatic Expansion Valve
Electrical Components	Eaton	Eaton	Eaton
Pump Included	✓	✓	✓
BMS Connectivity	Option	Option	Option
Web Interface Card	x	x	x
Fan Speed Controller	Yes	Yes	Yes
Closed Loop Option	✓	✓	✓
Flow Protection	Switch	Switch	Switch
Pressure Sensors	Semi Auto Reset Switch / Transducer	Semi Auto Reset Switch / Transducer	Semi Auto Reset Switch / Transducer
Phase Fail Protection	✓	✓	✓
Data Logging	Alarms Only	Alarms Only	Alarms Only
Mounting Options	Castors (Feet optional)	Adjustable Feet	Adjustable Feet
Redundancy configurations available	x	x	x

At Aqua Chiller we understand that every project has unique cooling requirements. That's why we offer a diverse range of industrial chillers, - each series designed with specific features to meet varying demands. Whether you need compact indoor chillers, high-performance outdoor units, or robust solutions for large-scale applications, our range has you covered. Additionally, we provide customisation options to tailor any chiller to your exact specifications, ensuring optimal performance for your specific project needs. Use the table below to compare key features across our chiller ranges and find the perfect solution for your application.

 Apex™	 Zeus™	 GLADIATOR
Premium chiller, matches capacity to heat load automatically for maximum efficiency	Utilises screw compressors for large cooling capacity requirements	Simple, yet effective range of reliable value based chillers
20kW to 100kW as standard Larger options available	155kW to 320kW as standard Larger options available	1kW to 200kW as standard
3 years	3 years	1 year
Yes	Yes	Option
Indoor/Outdoor	Indoor/Outdoor	Indoor/Outdoor
R410a	R134a	R134a
✓	✓	✓
Brazed Plate Pack HX	Shell and Tube HX	Coil in Tank, Plate Pack
Carel pCO5	Carel pCO5	Basic PCB
✓	Option	✓
Danfoss Variable Speed Scroll	Bitzer/Frescold Twin Screw	Panasonic/Emerson/Danfoss Reciprocating or Scroll
0%, then stepless from 25% to 100%	0%, then stepless from 50% to 100%	0/50/100% (Model Dependant)
Electronic Expansion Valve	Electronic Expansion Valve	Capillary/Thermostatic Expansion Valve
Eaton	Eaton	Schneider
✓	Option	✓
Option	Option	Option
Option	Option	x
EC Fans	HP Control	HP Control
✓	Standard	✓
Switch	Switch	Switch
Semi Auto Reset Switch / Transducer	Semi Auto Reset Switch / Transducer	Manual Switch
✓	✓	✓
Alarms Only, Optional pCO Web Card Upgrade	Alarms Only, Optional pCO Web Card Upgrade	Alarms Only
Adjustable Feet	Adjustable Feet	Castors, Skid
Option	Option	x

## Notes

- (a) Onsite commissioning included in metro areas only. Additional travel fees apply for areas outside of metro regions and will be specified on quotation.
- (b) 3 year warranty valid when unit installed to our specifications verified by Aqua Chiller commissioning visit. 6 month maintenances must be completed and logged on our website by qualified personnel. Annual water treatment and filter changes must occur with proof provided. Aqua Chiller can offer install and maintenance packages to suit.